



PCT/GB 2003 / 0 0 4 1 8 0



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 18 NOV 2003

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


BEST AVAILABLE COPY

Signed

*Andrew Gersen*


Dated

7 November 2003



# Patents Form 1/77

Patents Act 1977  
(Rule 16)



06FEB03 E782773-1 D02813  
P01/7700 0.00-0302670.5

1/77

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1.	Your Reference	P58851V		
2.	Patent Application number (The Patent Office will fill in this part)	0302670.5		
3.	Full name, address and postcode of the or each applicant (underline all surnames)	Hugh Stephen Freestone 108 Balcombe Road Horley Surrey RH6 9BW		
	Patents ADP Number (if you know it)	8478398001		
	If the applicant is a corporate body, give the country/state of its incorporation			
4.	Title of the invention	Devices for Protection against Adverse Weather Conditions		
5.	Name of your agent (if you have one)	FRY HEATH & SPENCE LLP		
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	The Gables Massetts Road Horley Surrey RH6 7DQ United Kingdom		
	Patents ADP Number (if you know it)	05880273001 08459554001		
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number.	Country	Priority application number (if you know it)	Date of filing (day / month / year)
		GB	0223157.9	5 October 2002
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application.	Number of earlier application	Date of filing (day / month / year)	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:	No		
	a) any applicant named in part 3 is not an inventor; or			
	b) there is an inventor who is not named as an			
	c) applicant, or			
	d) any named applicant is a corporate body			
	(See note (d))			

# Patents Form 1/77

Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form 0  
Description 8 ✓  
Claim(s) 4 ✓  
Abstract 1 ✓  
Drawing(s) 9 + 9 ✓

10. If you are also filing any of the following, state how many against each item.

Priority documents 0  
Translations of priority documents 0  
Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) 0  
Request for preliminary examination and search (*Patents form 9/77*) 0  
Request for substantive examination (*Patents form 10/77*) 0  
Any other documents 0  
(*please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

*Victoria J Townsend*

4 February 2003

12. Name and daytime telephone number of person to contact in the United Kingdom  
Victoria J Townsend  
01293 776880

## Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you filing or applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

## Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

## **DEVICES FOR PROTECTION AGAINST ADVERSE WEATHER CONDITIONS**

This invention relates to devices for protection against adverse weather conditions including foldable umbrellas and devices of similar configuration such as parasols or sun shades.

Umbrellas and parasols are well known and typically take the form of a foldable framework which, when erected, has stretched over it a sheet of material which provides a protective cover against rain, sun or other undesirable weather. In the case of umbrellas the material is normally water resistant. The frame of these known devices comprises a handle portion which, when the device is erect, extends from the centre of the stretched material, the stretched material forming a typically domed surface at the top of the handle portion when the device is in use. A number of support arms extend from the handle portion beneath the stretched material when the device is in use so as to support the domed surface.

For maximum protection from adverse weather conditions such as heavy rain, snow, or strong sunlight, a user would desirably position himself at the centre of the protective domed surface of these known devices, this however is difficult when the only means for holding the device extends from the centre of the domed surface.

The present invention provides a device for protection against adverse weather conditions comprising; a framework foldable between a storable configuration and an erect configuration and a sheet of weather resistant material mounted on the frame, the sheet of weather resistant material forming, when the frame is in its erect configuration, a protective cover which can be positioned over a user to protect against adverse weather conditions, wherein, when erect, the frame is supported by a handle which extends from a position which is spaced apart from the centre of the erected frame.

Desirably, the handle extends from a position at or adjacent to an

outer edge of the protective cover.

By repositioning the handle of these common devices, the inventor has created a device where more efficient use of the surface area of the protective cover can be made for shielding a user against adverse weather conditions. The novel arrangement not only provides a more convenient to use device for the user but can reduce the overall quantity and complexity of materials to be used in the manufacture of such a device rendering it cheaper and easier to manufacture than the known arrangements described above.

The framework of the novel device may comprise a main support strut and a plurality of additional support struts which are pivotable about a common axis, shared by the main support strut such that they can be fanned out from a storable configuration where they are substantially in alignment with one another to an erect configuration where each additional strut extends radially at a different rotational position on a circle having its centre at the common axis. A handle portion is optionally connected to one of the struts, desirably positioned at or adjacent an end of the strut which is opposed to the end at which the struts are pivotable. The handle is desirably itself hinged and/or hingedly connected to the strut. The handle can conveniently be connected to the main support strut.

Desirably, the main support strut is of substantially the same length as the additional support struts, this is not, however essential.

In an alternative embodiment, the frame and optionally also the handle may comprise a single moulded piece. In such an arrangement, the main supporting and each of the additional struts are connected by a series of flexible links known as "live hinges", which, when the frame is erected, encircle a centre point about which all the struts are pivotable. The circle formed by the live hinges when the frame is erect can be capped by a domed cap of diameter slightly greater than the circle formed by the live hinges. The domed cap may include a plug for snap fitting or fastening into a socket

provided within the circle formed by the live hinges. Typically the moulded frame and cap comprise the same material, desirably the material is a plastics material, for example a polyvinyl chloride (PVC) or a polyethylene (PE). The handle may also be foldable by means of a live hinge. Optionally the handle is hingedly connected to the frame by means of a live hinge. When the handle is extendable/foldable by means of a live hinge, the live hinge desirable has associated therewith a catch for securing the hinge in its closed position (which corresponds to an extended configuration of the handle).

The sheet of weather resistant material is secured to the main support strut and extends over each of the additional support struts such that when the struts are fanned out to the erect configuration, the material is stretched out to form a substantially smooth surface. The quantity of material is sufficient to close a circular area formed by the support struts when the framework is in its erect configuration. That is not to say that the shape of the protective cover need be circular, indeed it may be polygonal, square or any one of a number of geometric shapes into which a circle may be fitted.

The sheet of weather resistant material may include a flap at either or both of its ends which meet when the device is fanned out to its fully erect configuration. The flaps are preferably fixable onto the opposite end of the sheet so as to provide a leak proof join between the ends. The flaps may be fixable by any known means which may include but are not strictly limited to; press studs, hook and eye, Velcro™ or the like.

The sheet of weather resistant material may be selected according to the preferred application of the device. For example, if the device is for use against rain, sleet or snow then the material may be waterproof. Where the device is primarily for use as a sunshade, the material may be substantially opaque.

In a simple embodiment the struts may fan out in a horizontal plane, optionally, however, the struts may be arranged to fan at an angle to the

horizontal so as to provide a substantially dome or cone shaped surface over which the sheet of weather resistant material is stretched. This may provide for better dispersion of weather elements such as rain, sleet or snow. The cone or dome shape can be achieved by providing struts which are slightly curved at the end at which they are pivotally mounted, or by using flexible struts which, when erect, will bend under their own weight.

Desirably, the framework is provided with one or more locking mechanisms for locking the erected framework into position. Optionally, the one or more locking mechanisms may comprise a catch provided on the main support strut for catching an additional support strut when the support struts have been fanned out. The one or more locking mechanisms may further comprise a locking mechanism for locking the handle portion in its desired position for holding the device. The device may also include one or more locking mechanisms for locking the device in its storable configuration for ease of storage and transportation.

A locking mechanism for locking the handle in the upright configuration may comprise a collet portion which can be radially contracted for insertion through a collar and radially extended or biased to grip the collar from the inside.

Optionally, the handle portion may itself be collapsible, for example but not limited to, by being foldable or telescopically extendable and retractable.

For the purposes of clarification, some embodiments of the invention will now be described by way of example only and with reference to the following Figures in which:

Figure 1 illustrates the framework of a first embodiment of the invention in a fully erect configuration;

Figure 2 illustrates the framework of an embodiment similar to that of

Figure 1 in a partially erect configuration;

Figure 3 illustrates the framework of an embodiment similar to that of Figure 1 and Figure 2 in a collapsed configuration;

Figure 4 illustrates in general overview the framework of an alternative embodiment to that of Figures 1 to 3;

Figure 5 illustrates in more detail a locking mechanism for securing the framework of the embodiment of Figure 4 in its erect configuration;

Figures 6a and 6b illustrate in more detail a mechanism for securing the handle to the framework of the embodiment of Figure 4;

Figure 7 illustrates in more detail the connections between adjacent struts of the framework of the embodiment of Figure 4;

Figure 8 illustrates in more detail the centre of the framework of the embodiment of Figure 4 when in its erect configuration;

Figure 9 illustrates in more detail the handle of the embodiment of Figure 4.

As can be seen from Figure 1 an embodiment of the device according to the invention comprises essentially of a handle portion 10 attached by means of a hinge 12 to a main support strut 11 of the main cover support frame. A plurality of additional support struts S1, S2, ....S6 are pivotally mounted about a common pin 15 carried by the main support strut 11. A sheet of weather resistant material 16 is webbed between each of the struts in such a manner that when the frame is fully erect as shown in Figure 1, the weather resistant material is stretched taught to provide a robust, protective cover against inclement weather conditions. The handle 10 comprises a telescopically extendable pole having a gripping portion 10a at one end.



As can be seen from Figure 2, the main frame of the device is erected by simply fanning the additional support struts S1,...S6 about the pin 15. The outermost strut S6 can then be secured into position adjacent the main support strut 11 by a clip 14 provided on the main support strut 11. Also provided on the main support strut 11 is a second clip 13 which fixes the handle in an erected position substantially perpendicular to the main support strut 11.

As shown in Figure 3, the main support strut 11 has an essentially L shaped cross section with a pin 15 standing parallel to the long side of the L and extending perpendicularly from the shorter side of the L. It is to be understood that the L may be equally arranged to be upside down relative to its position as shown in the Figure without materially affecting the operation of the device. The pin is positioned adjacent one end of the main support strut. The additional support struts S1, S2, .....S6 are each pivotally mounted on the pin, the pivot point is in each case positioned adjacent one end of the strut and the struts are stacked one above the other. When the device is in its collapsed condition as shown in Figure 3, the additional support struts align and are received within the L shaped main support strut for compactness. The weather resistant cover 16 is folded and tucked behind the additional support struts, adjacent the long side of the L of the main support strut.

The telescopically extending handle is retracted to a length which is not much longer than the main support strut and folded into substantially parallel alignment with the main support strut by means of hinge 12. This results in a flat compact unit for transport and storage.

Figures 4 to 9 illustrate an alternative embodiment which is advantageous in that it's framework can be cheaply and easily manufactured from a small number of moulded components.

As can be seen from Figure 4, in common with the foregoing embodiments, this embodiment comprises a plurality of struts 41, S1, S2,.....,S8 sharing a common axis about which each is pivotable. However, in this arrangement the struts are all connected by flexible links or "live hinges" better shown in Figure 7. When the frame is erected, the links form a circle concentric about the common axis. A mushroom shaped plug 40 encloses the circle.

A main supporting strut 41 carries a collar 43 with an axis substantially parallel to the common axis. The collar 43 forms part of a connector for connecting a handle 42 to the frame 41, S1, S2,.....,S8. The connector is better illustrated in Figures 5 and 6b. the collar is shown in more detail in Figure 6a.

As can be seen from the Figure, when the frame is in its erected configuration, a terminal strut S8 meets with the main strut 41. As shown in more detail in Figure 5, the main 41 and terminal S8 struts are provided respectively with an upper 41a and a lower S8a surface shaped to engage with the opposed surface of the other strut. In addition, each of these struts has a protrusion 41b, S8b extending from the end of the strut furthest removed from the common axis. The protrusions are each provided with a ribbed surface 41c, S8c. The protrusions are configured to provide a convenient gripping means which may be used by a user erecting the frame to draw the main and terminal struts together with a one handed grip. Once drawn together, the two struts 41 and S8 can be secured together by fastening of a catch 44 which is hingedly connected (again by means of a live hinge) to the terminal strut and is configured to hook across an end surface of the main support strut and snap fit to the end of the main support strut whereby to fix the frame in its erect configuration.

As can be seen from Figures 6 and 6a, the handle 42 of the device comprises at one end a collet 62 which is receivable in the collar 43 and is resiliently biased, when inserted into the collar 43, to grip the collar 43 from

the inside. The collet 62 is desirably provided with a ridged or flanged end which, when the handle 42 is pulled so as to remove the collet 62 from the collar 43 without first radially contracting the collet 62, tends to resist removal of the handle 42. Adjacent the collet 62, it can be seen the handle 42 comprises a live hinge 61 which allows the handle 42 to be folded from the position shown in the Figure in the direction of the arrow. When the handle 42 is in its erect configuration as shown in the Figure, a catch 63 snaps the hinge 61 shut. The catch 63 is similar in configuration to the catch 44. The catch 63 is provided with a levered section 63a which the user may use to open the hinge 61 and fold the handle 42.

Figures 7 and 8 show in more detail the arrangement of live hinges which link together the struts 41, S1, S2.....S8. Moulded to the arrangement of live hinges is a socket 71 into which can be received a plug 81 of a domed or mushroom shaped cap 82 which, in use, serves to enclose the circular space formed by the hinges when the framework is in its erect configuration. The cap 82 may also serve to hold in place a sheet of weather resistant material which will, as previously described, be mounted on the frame.

Figure 9 shows the handle of the foregoing embodiment in more detail. It can be seen the handle 42 is moulded to provide a convenient and comfortable gripping surface 42a to be embraced by the hand of a user.

## CLAIMS

1. A device for protection against adverse weather conditions comprising; a framework foldable between a storable configuration and an erect configuration and a sheet of weather resistant material mounted on the frame, the sheet of weather resistant material forming, when the frame is in its erect configuration, a protective cover which can be positioned over a user to protect against adverse weather conditions, wherein, when erect, the frame is supported by a handle which extends from a position which is spaced apart from the centre of the erected frame.
2. A device as claimed in claim 1 wherein the handle extends from a position which is at or adjacent to an outer edge of the protective cover.
3. A device as claimed in claim 1 or 2 wherein the framework comprises a main support strut and a plurality of additional support struts which are pivotable about a common axis, shared by the main support strut such that the additional support struts can be fanned out from a storable configuration where they are substantially in alignment with one another to an erect configuration where each additional strut extends radially at a different rotational position on a circle having its center at the common axis.
4. A device as claimed in claim 3 wherein the main supporting and each of the additional struts are connected by a series of flexible links, which, when the frame is erected, encircle a centre point about which all the struts are pivotable.
5. A device as claimed in claim 4 wherein the circle formed by the flexible links when the frame is erect is capped.

6. A device as claimed in claim 6 wherein the domed cap includes a plug receivable in a socket provided within the circle formed by the live hinges.
7. A device as claimed in claim 6 wherein the frame and cap comprise the same material.
8. A device as claimed in any preceding claim wherein the frame comprises a plastics material.
9. A device as claimed in any preceding claim wherein the plastics material is selected from polyvinyl chloride (PVC) or a polyethylene (PE).
10. A device as claimed in any of claims 3 to 9 wherein the handle is itself hinged and/or is hingedly connected to a strut.
11. A device as claimed in any of claims 3 to 10 claim wherein the handle is connected to the main support strut.
12. A device as claimed in any preceding claim wherein the handle is at least in part, telescopically extendable and retractable.
13. A device as claimed in any of claims 3 to 12 wherein the additional support struts fan out in a substantially horizontal plane.
14. A device as claimed in any of claims 3 to 13 wherein the additional support struts are arranged to fan out at an angle to the horizontal so as to provide a substantially dome or cone shaped surface over which the sheet of weather resistant material is stretched.
15. A device as claimed in any preceding claim wherein the sheet of weather resistant material includes a flap at either or both of its ends

which meet when the device is fanned out to its fully erect configuration.

16. A device as claimed in claim 10 wherein the flap or flaps are fixable onto the opposite end of the sheet so as to provide a leak proof join between the ends of the sheet when the device is in its fully erect configuration.
17. A device as claimed in claim 15 or claim 16 wherein the flaps are fixable by means selected from press studs, hook and eye or Velcro<sup>TM</sup>.
18. A device as claimed in any preceding claim wherein the sheet of weather resistant material is water resistant.
19. A device as claimed in any preceding claim wherein the sheet of weather resistant material is substantially opaque.
20. A device as claimed in any preceding claim wherein the framework is provided with one or more locking mechanisms for locking the erected framework into position.
21. A device as claimed in claim 20 wherein the one or more locking mechanisms comprises a catch configured for securing the main support strut to an additional support strut when the support struts have been fanned out.
22. A device as claimed in any preceding claim wherein the framework is provided with one or more locking mechanisms for locking the handle portion in its desired position for holding the device.
23. A device as claimed in any preceding claim wherein the device includes one or more locking mechanisms for locking the device in its storable configuration for ease of storage and transportation.

24. A device as claimed in any preceding claim wherein the handle is detachably connected to the frame.
25. A device as claimed in claim 24 wherein the handle is provided at one end with a collet which is receivable in a collar provided on the frame and is resiliently biased, when inserted into the collar, to grip the collar from the inside.
26. A device as claimed in claim 25 wherein the collet has a ridged or flanged end which, when the handle is pulled so as to remove the collet from the collar without first radially contracting the collet, tends to resist removal of the handle.
27. A device as claimed in any of claims 3 to 26 wherein the additional struts include a terminal strut which meets with the main strut, the main and terminal struts being provided respectively with an upper and a lower surface shaped to engage with the opposed surface of the other strut, each of these struts having a protrusion extending from the end of the strut furthest removed from the common axis the protrusions each being provided with a ribbed surface and being configured to provide a convenient gripping means which may be used by a user erecting the frame to draw the main and terminal struts together with a one handed grip.
28. A device substantially as described herein with reference to the Figures 1, 2 or 3.

**ABSTRACT**  
**DEVICES FOR PROTECTION AGAINST ADVERSE WEATHER**  
**CONDITIONS**

A device for protection against adverse weather conditions comprising; a framework (11, S1, S2, ....S6) foldable between a storable configuration and an erect configuration and a sheet of weather resistant material (16) mounted on the frame, the sheet of weather resistant material forming, when the frame is in its erect configuration, a protective cover which can be positioned over a user to protect against adverse weather conditions, wherein, when erect, the frame is supported by a handle (10) which extends from a position at or adjacent to an outer edge of the protective cover.

[Fig.1]





Fig. 2





FIG. 3






Fig 4.




Fig 5






Fig 6b






Fig 8.






Fig 9

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**